PLASMA & LCD CARTS



DIMENSIONS:

Load Capacity: 375 lbs

EXTERIOR

Height - 32"

Width - 76"

Depth - 31"

INTERIOR

Height - 17 1/2"

Depth - 23"

Rack to Glass - 1 7/8"

Rack Width - 19"

Rack Units - 10RUs

SHIPPING BOX (Palletized)

Length- 50"

Width - 40"

Height - 84"

Ship Weight - 312 lbs





The GMP-350L is 32" tall and holds a single display up to 65" or dual displays up to 55". Comes standard with 10RU 19" rack mount bracket in front and rear, 6 port APC® surge protector and adjustable shelf. At 23" deep, there is ample space to accommodate larger systems. Includes universal screen mounting system and set-top camera mount. Choose TT-1 or TT-2. Please include model number of screen(s) when

ordering.

GMP - 350L - TT1/ TT2

SOLID STEEL CARTS

The most **FEATURES** on the market:

- ▶ TT-1 for use with single display
- ► TT-2 for use with dual displays
- One adjustable interior rack mounted shelf
- ▶ 6 Port APC® surge protector
- Cable management features
- Tempered, tinted locking front glass door
- ▶ Bolted rear panel for easy access to equipment
- ▶ Deep interior space (23") for extra storage
- Standard 19" front and rear rack mount brackets,
 10RUs of space
- Standard adjustable v/c camera platform
- ▶ 32" Height for optimal face-to-face communication
- Large footprint to provide extra stability
- ▶ 5" Double truck ball bearing casters, two with brake
- ▶ 100% Solid steel construction
- Available for immediate shipping

Choose your **OPTIONS**:

- Additional rack mount shelf (US-1)
- ► Rack mounted M-Audio® speaker module (PSM-200)
- ► Heavy duty 6" caster upgrade
- Single gang Wall Plates (3 RCA, VGA+Audio and VGA+Audio+LAN)
- ► GM-9000 to accommodate deeper equipment
- ▶ 6 Port rack mount APC® surge protector (RCK-PWR)
- Custom cut Rack Shelf for Lifesize[®], Polycom[®] and Tandberg[®] codecs
- Revolabs® Shelving System in various configurations for wireless microphone integration

Furniture Engineered For Today's Technology

